

Silage sheets

All silage products have three layer co-extrusion LDPE film, great mechanical properties and strong resistance to tearing and impact. The film has been designed to cover fodder and preserve it to feed the cattle, keeping its original nutritional value. They provide very low permeability to oxygen and excellent barrier against water and air, avoiding possible leakage of polluting gases.

Black Silage Film (Standard range)

- Manufactured in thicknesses between 100 and 200 (400-800 gauges). Black opaque coloured.
- The black layer is responsible for providing an excellent opacity and works as a barrier to long I.R. radiation allowing it to maintain a well-balanced internal temperature.

8m x 50m (100mu) **CODE: VISB10**

8m x 28m (200mu) **CODE: VISB11**

Complete range of sizes available



Farm Film Stretchwrap

Tried and tested to withstand the extreme weather conditions ranging from harsh Nordic winters to high summer temperatures of continental Europe and the wet climates of Britain and Ireland. Unique triple layer construction, instant bond and long term adhesion, eliminating "tailing" after wrapping and complete air-fastness for minimum of 12 months. Even colour dispersion without stretch marks and windowing. Unique additive package for long-term protection against film breakdown. High tack and impact strength for use on all balewrappers - round or square, static or trailed, semi or fully auto.

Width: 500mm, 750mm
Length per roll: 1500m, 1800m
Colour: Black or green

Black 500mm **CODE: SILAFLEX**
Black 750mm **CODE: SILAFLEX7**
Green 500mm **CODE: POLY16**
Green 750mm **CODE: POLY17**